

View Online at <https://aerobasegroup.com/nsn/5925-00-810-4912>

Overall Length:

6.000 inches

Overall Height:

3.812 inches

Overall Width:

3.000 inches

Case Material:

Plastic

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac all locations and 40.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Ultimate Trip Time Per Pole In Seconds:

300.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

300.000 at 150 pct all locations and 60.000 at 200 pct all locations and 5.000 at 500 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Mtg holes spaced 4.844 in. C to c

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0