## NSN 5925-00-818-4811



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-818-4811 **Body Style:** Single pole type **Body Length:** 3.000 inches **Body Width:** 0.730 inches **Body Height:** 2.310 inches **Case Material: Plastic Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity: Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** 

Manual

**Main Contact Tripping Mechanism Type:** 

Trip free

**Manual Actuator Type And Quantity:** 

1 toggle

**Actuator Function:** 

Trip w/separate reset

**Actuator Position Designation:** 

At pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:** 

18.000 at 200 pct single location and 35.000 at 200 pct single location

## NSN 5925-00-818-4811

Circuit Breaker - Page 2 of 2



Trin	Release	<b>Ambient</b>	<b>Tempurature</b>	Rating:
III	Neicase		I CIIIDUI ALUI C	ivatilia.

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

**Terminal Type And Quantity:** 

1 pin and 1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0