

View Online at <https://aerobasegroup.com/nsn/5925-00-819-1098>

Body Style:

Rectangular dimensional envelope

Overall Length:

4.688 inches

Overall Height:

1.675 inches

Overall Width:

2.578 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.203 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Automatic

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip single location

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 200.000 at 200 pct single location

Inclsoure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit single location

Switch Terminal Type:

Screw

Switch Current Rating And Type In Amps:

10.0 dc

Switch Voltage Rating And Type In Volts:

28.0 dc

Special Features:

Designed for use with klixon 3mc circuit breakers

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

15.000 ounces

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0