

View Online at <https://aerobasegroup.com/nsn/5925-00-819-1098>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

4.688 inches

**Overall Height:**

1.675 inches

**Overall Width:**

2.578 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

175.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Automatic

**Auxiliary Switch Function And Quantity:**

1 control

**Internal Trip Release Configuration:**

Series trip single location

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location and 200.000 at 200 pct single location

**Inclsoure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

77.0 degrees fahrenheit single location

**Switch Terminal Type:**

Screw

**Switch Current Rating And Type In Amps:**

10.0 dc

**Switch Voltage Rating And Type In Volts:**

28.0 dc

**Special Features:**

Designed for use with klixon 3mc circuit breakers

**Frequency In Hertz:**

60.0 single location

**Unpackaged Unit Weight:**

15.000 ounces

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0