

View Online at <https://aerobasegroup.com/nsn/5925-00-821-5373>

**Body Length:**

2.631 inches

**Body Width:**

2.187 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.422 inches and 1.452 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.860 inches and 0.890 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.797 inches and 1.827 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.860 inches and 0.890 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

Between 2.422 inches and 2.452 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

90.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1200.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 200 pct all locations and 65.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed and shock resistant and vibration resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

86.000 pounds

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0