NSN 5925-00-823-2509

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-823-2509

Body Style:
Rectangular dimensional envelope
Overall Length:
13.094 inches
Overall Height:
4.062 inches
Overall Width:
8.250 inches
Unthreaded Mounting Hole Diameter:
0.312 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
225.0 amperes ac all locations and 225.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations and 250.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
93.000 at 200 pct all locations and 550.000 at 200 pct all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:

6 compression

NSN 5925-00-823-2509

Circuit Breaker Tripper - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0