

View Online at <https://aerobasegroup.com/nsn/5925-00-826-8774>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.365 inches and 0.385 inches

Body Length:

Between 1.552 inches and 1.572 inches

Body Width:

Between 1.271 inches and 1.291 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.865 inches and 0.885 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.615 inches and 0.635 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 1.690 inches and 1.710 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

500.0 milliamperes dc first location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 5.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Explosion resistant and fungus resistant and hermetically sealed

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0