NSN 5925-00-828-3530

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-828-3530 **Body Style:** Multipole-multiple actuator type **Body Length:** 3.344 inches **Body Width:** 2.000 inches **Body Height:** 2.312 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.188 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 terminal **Storage Type:** General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 70.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

Manual Actuator Type And Quantity: 2 toggle

NSN 5925-00-828-3530 Circuit Breaker - Page 2 of 2



Actuator Function: Trip-reset Actuator Position Designation: At each pole External Actuator Linkage Arrangement: One and two linked Trip Delay Time In Seconds Per Rated Continuous Current: 360.000 at 200 pet all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Actuator Position Designation: At each pole External Actuator Linkage Arrangement: One and two linked Trip Delay Time In Seconds Per Rated Continuous Current: 360.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
At each pole External Actuator Linkage Arrangement: One and two linked Trip Delay Time In Seconds Per Rated Continuous Current: 360.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
External Actuator Linkage Arrangement: One and two linked Trip Delay Time In Seconds Per Rated Continuous Current: 360.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
One and two linked Trip Delay Time In Seconds Per Rated Continuous Current: 360.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Trip Delay Time In Seconds Per Rated Continuous Current: 360.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
360.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Fungus resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Frequency In Hertz: 60.0 all locations Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	nat
Terminal Type And Quantity: 2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	d
2 clip and 2 compression Specification Data: 81348-w-c-375/14 government specification	
Specification Data: 81348-w-c-375/14 government specification	
81348-w-c-375/14 government specification	
0. 414	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	