NSN 5925-00-833-2703



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-833-2703 **Body Style:** Rectangular dimensional envelope **Overall Length:** 6.000 inches **Overall Height:** 3.969 inches **Overall Width:** 4.125 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.188 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac all locations and 50.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations and 5000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 200.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:**

Trip-reset

Actuator Position Designation:

At pole two

NSN 5925-00-833-2703

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Shunt trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
60.0 all locations
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0