NSN 5925-00-833-2703

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-833-2703

Body Style:

Rectangular dimensional envelope

Overall Length:

6.000 inches

Overall Height:

3.969 inches

Overall Width:

4.125 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations and 50.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

NSN 5925-00-833-2703

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration: Shunt trip all locations Inclosure Protection Type For Which Designed: General purpose Frequency In Hertz: 60.0 all locations **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Terminal Type And Quantity: 6 screw Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A030a0