## NSN 5925-00-833-7954

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-833-7954 **Body Style:** Multipole-single actuator type **Body Length:** 6.310 inches **Body Width:** 2.750 inches **Body Height:** 3.380 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.250 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.880 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.188 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac all locations and 20.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Thermal all locations

**Trip Release Characteristic:** 

Instantaneous all locations and time delay all locations

## **NSN 5925-00-833-7954** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
18.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0