## NSN 5925-00-835-0257



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-835-0257 **Body Style:** Rectangular dimensional envelope **Overall Length:** 6.000 inches **Overall Height:** 1.500 inches **Overall Width:** 3.594 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.250 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 3 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location and 20.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location and 120.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location and 5000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 120.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

**Actuator Function:** 

Trip-reset

## **NSN 5925-00-835-0257** Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0