NSN 5925-00-835-6008



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-835-6008 **Body Style:** Multipole-multiple actuator type **Body Length:** 3.281 inches **Body Width:** 3.000 inches **Body Height:** 2.922 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.219 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Storage Type:** General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual

Main Contact Tripping Mechanism Type: Trip free

NSN 5925-00-835-6008 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
5.100 ounces
Terminal Type And Quantity:
6 bus bar
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0