NSN 5925-00-837-8662

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-837-8662

Body Style:

Single pole type

Body Length:

Between 2.484 inches and 2.516 inches

Body Width:

Between 0.734 inches and 0.766 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.876 inches and 2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.046 inches and 2.078 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.109 inches and 0.141 inches

Mounting Surface To Terminal End Distance:

2.690 inches

Pole Quantity:

.

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

400.0 milliamperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

NSN 5925-00-837-8662 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
6.000 at 200 pct single location and 60.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant and explosion resistant
Frequency In Hertz:
400.0 single location
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0