# NSN 5925-00-839-0293

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-839-0293

# **Body Style:**

Rectangular dimensional envelope

# **Overall Length:**

7.531 inches

# **Overall Height:**

3.500 inches

# **Overall Width:**

3.688 inches

#### **Unthreaded Mounting Hole Diameter:**

0.438 inches

# **Pole Quantity:**

3

#### Mounting Facility Type And Quantity:

3 unthreaded hole

#### Features Provided:

Adjustable trip release

# Maximum Continuous Load Current Rating Per Pole:

250.0 amperes ac all locations and 250.0 amperes dc all locations

# Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

# Circuit Protection Type:

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

# **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

# Adjustable Trip Setting Current Range Per Pole In Amps:

+650.0/+1300.0 ac all locations and +650.0/+1300.0 dc all locations

# Trip Delay Time In Seconds Per Rated Continuous Current:

1200.000 at 150 pct all locations and 60.000 at 300 pct all locations and 120.000 at 300 pct all locations

# Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

#### **Frequency In Hertz:**

60.0 all locations

# **Terminal Type And Quantity:**

6 bus bar

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5925-00-839-0293

Circuit Breaker Tripper - Page 2 of 2

Demilitarization:

No

Fiig:

A030a0

