

View Online at <https://aerobasegroup.com/nsn/5925-00-839-7879>

Overall Length:

3.265 inches

Overall Height:

5.343 inches

Overall Width:

1.025 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.164 inches

Pole Quantity:

1

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

80.000 single location and 400.000 single location

Reset Method:

Automatic

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Trip Delay Time In Seconds Per Rated Continuous Current:

80.000 at 125 pct single location and 400.000 at 125 pct single location and 19.000 at 200 pct single location and 60.000 at 200 pct single location and 6.000 at 300 pct single location and 9.000 at 300 pct single location

Special Features:

Mounting hole/stud quani type 1

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0