

View Online at <https://aerobasegroup.com/nsn/5925-00-841-0679>

Body Style:

Multipole-single actuator type

Bushing Length:

0.281 inches

Body Length:

0.850 inches

Body Width:

2.000 inches

Body Height:

2.765 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches

Center To Center Distance Between Terminals Parallel To Width:

1.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.810 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing and 4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32 and 32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

800.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches and 0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 35.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unef and unc

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0