## NSN 5925-00-843-0306

Circuit Breaker - Page 1 of 2

**Body Style:**Single pole type



View Online at https://aerobasegroup.com/nsn/5925-00-843-0306

Mounting Slot Width:
0.370 inches
Body Length:
6.310 inches
Body Width:
1.375 inches
Body Height:
3.188 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.880 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.187 inches
Boss Height:
0.125 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
4 slot
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
Maximum Continuous Load Current Rating Per Pole:  15.0 amperes ac single location and 15.0 amperes dc single location
_
15.0 amperes ac single location and 15.0 amperes dc single location
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:  Overcurrent single location
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:  Overcurrent single location  Trip Release Method:
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:  Overcurrent single location  Trip Release Method:  Thermal-magnetic single location
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:  Overcurrent single location  Trip Release Method:  Thermal-magnetic single location  Trip Release Characteristic:
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:  Overcurrent single location  Trip Release Method:  Thermal-magnetic single location  Trip Release Characteristic:  Instantaneous single location and time delay single location
15.0 amperes ac single location and 15.0 amperes dc single location  Operating Voltage Type And Rating Per Pole In Volts:  277.0 ac single location and 125.0 dc single location  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac single location  Circuit Protection Type:  Overcurrent single location  Trip Release Method:  Thermal-magnetic single location  Trip Release Characteristic:  Instantaneous single location and time delay single location  Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

## **NSN 5925-00-843-0306** Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0