NSN 5925-00-845-2965



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-845-2965 **Body Length:** 15.500 inches **Body Width:** 8.250 inches **Body Height:** 5.500 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 14.250 inches **Center To Center Distance Between Terminals Parallel To Width:** 2.770 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 14.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.770 inches **Boss Height:** 0.219 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 600.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 25000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations

Trip Release Method: Magnetic all locations **Trip Release Characteristic:**

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

NSN 5925-00-845-2965 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
22.000 at 100 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0