

View Online at <https://aerobasegroup.com/nsn/5925-00-851-2849>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.250 inches

**Body Length:**

2.250 inches

**Body Width:**

2.203 inches

**Body Height:**

2.125 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.187 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.486 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.486 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.812 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac all locations and 50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac all locations and 28.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1.500 ac all locations and 2.500 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 70.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Explosion resistant and moisture resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Test Data Document:**

81349-mil-c-5809 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 tab w/screw

**Specification Data:**

96906-ms21984 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0