# NSN 5925-00-852-2820

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-852-2820

## Body Style:

Multipole-multiple actuator type

#### **Body Length:**

2.500 inches

## Body Width:

1.500 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

#### Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

## 0.750 inches

Fragility Factor:

Moderately rugged

## **Boss Height:**

0.140 inches

## Mounting Surface To Terminal End Distance:

2.611 inches

#### Pole Quantity:

2

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 threaded hole

# Storage Type:

General purpose warehouse

# Thready Qty Per Inch (tpi):

32

## Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic-hydraulic all locations

# NSN 5925-00-852-2820

Circuit Breaker - Page 2 of 2



**Trip Release Characteristic:** 

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

**Reset Method:** 

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

**Actuator Position Designation:** 

At each pole

**External Actuator Linkage Arrangement:** 

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current: 0.200 at 200 pct all locations and 1.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Fungus resistant and moisture resistant and explosion resistant Frequency In Hertz: 60.0 all locations Thread Series Designator: Unc Terminal Type And Quantity: 4 threaded stud Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0