

View Online at <https://aerobasegroup.com/nsn/5925-00-852-7809>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

11.656 inches

**Overall Height:**

8.875 inches

**Overall Width:**

11.000 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Thread Qty Per Inch (tpi):**

20

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations and 100.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations and 250.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.250 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

120.000 at 200 pct all locations and 360.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0