## NSN 5925-00-856-4818

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-856-4818 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** 1.152 inches **Body Width:** 0.750 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** Between 1.173 inches and 1.203 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.859 inches **Pole Quantity:** 1 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 2.0 amperes ac single location and 2.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 200.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location and 2500.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 single location **Reset Method:** 

Manual

## **NSN 5925-00-856-4818** Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.468 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.400 at 200 pct single location and 1.800 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
0.125 pounds
Precious Material And Location:
Terminal surfaces silver
Precious Material:
Silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0