NSN 5925-00-856-8103

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-856-8103

| Body Style: |
|--|
| Multipole-multiple actuator type |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 2.250 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.938 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 0.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.062 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.750 inches |
| Boss Height: |
| 0.140 inches |
| Mounting Surface To Terminal End Distance: |
| 2.471 inches |
| Pole Quantity: |
| 3 |
| Arc Quenching Method: |
| Magnetic blowout |
| Mounting Facility Type And Quantity: |
| 6 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 26.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 208.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 1000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Magnetic-hydraulic all locations |
| Trip Release Characteristic: |
| Time delay all locations |

NSN 5925-00-856-8103 Circuit Breaker - Page 2 of 2

