

View Online at <https://aerobasegroup.com/nsn/5925-00-864-9405>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

2.273 inches

**Body Height:**

2.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.190 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.562 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.812 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

Between 1.990 inches and 2.010 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

208.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.300 at 200 pct all locations and 0.900 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Humidity resistant and vibration resistant and shock resistant and explosion proof and salt spray proof and fungus resistant and sand resistant and dustproof

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

0.810 pounds

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0