

View Online at <https://aerobasegroup.com/nsn/5925-00-865-1318>

Body Style:

Single pole type

Bushing Length:

0.280 mils and 0.300 centimeters

Body Length:

Between 1.735 inches and 1.765 inches

Body Width:

Between 0.615 inches and 0.635 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 1.328 inches and 1.358 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

250.0 milliamperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Thread Size:

0.469 inches

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant and humidity proof and salt spray proof and shockproof and vibrationproof and weatherproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Test Data Document:

13499-260-4035 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0