

View Online at <https://aerobasegroup.com/nsn/5925-00-867-7329>

Body Style:

Multipole-single actuator type

Body Length:

6.500 inches

Body Width:

4.125 inches

Body Height:

4.062 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.938 inches

Center To Center Distance Between Terminals Parallel To Width:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.827 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.688 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.188 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 200 pct all locations and 15.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Circuit breaker supplied with two threaded mounting screws

Frequency In Hertz:

400.0 all locations

Test Data Document:

81349-mil-c-17361 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 quick disconnect, male

Specification Data:

81349-mil-c-17361/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0