## NSN 5925-00-870-3582

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-870-3582

Body Style:
Multipole-single actuator type
Body Length:
6.000 inches
Body Width:
4.500 inches
Body Height:
3.594 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.094 inches
Center To Center Distance Between Terminals Parallel To Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.500 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
30.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
208.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:

Instantaneous all locations and time delay all locations

## NSN 5925-00-870-3582

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
18.000 at 200 pct all locations and 52.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A030a0