

View Online at <https://aerobasegroup.com/nsn/5925-00-872-6522>

Body Style:

Rectangular dimensional envelope

Overall Length:

Between 1.802 inches and 1.822 inches

Overall Height:

Between 0.615 inches and 0.635 inches

Overall Width:

Between 1.178 inches and 1.198 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.175 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac first location

Operating Voltage Type And Rating Per Pole In Volts:

150.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 200 pct all locations and 50.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0