

View Online at <https://aerobasegroup.com/nsn/5925-00-874-0952>

Body Style:

Multipole-multiple actuator type

Mounting Slot Width:

0.190 inches

Body Length:

1.820 inches

Body Width:

3.150 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Any acceptable

Center To Center Distance Between Terminals Parallel To Width:

Any acceptable

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.760 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

2.650 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 slot

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

380.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

60.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 all locations

Reset Method:

Automatic

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

2 alarm

Internal Trip Release Configuration:

Series trip all locations

Switch Location And Position Designation:

Internal at pole one and internal at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 45.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

20.0 degrees celsius all locations

Switch Current Rating And Type In Amps:

3.0 ac

Switch Voltage Rating And Type In Volts:

250.0 ac

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0