NSN 5925-00-883-7660

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-883-7660

Body Style: Single pole type **Body Length:** 2.500 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.190 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.812 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity:** 1 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:**

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

NSN 5925-00-883-7660 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
3.000 at 200 pct single location and 10.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
4.250 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0