

View Online at <https://aerobasegroup.com/nsn/5925-00-887-9380>

Body Style:

Single pole type

Bushing Length:

Between 0.381 inches and 0.401 inches

Body Length:

Between 1.803 inches and 1.823 inches

Body Width:

Between 0.553 inches and 0.573 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.146 inches and 1.168 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 2.240 inches and 2.260 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

27

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location and 5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50.0 ac single location and 50.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 40.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Waterproof and dustproof

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

0.062 pounds

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0