NSN 5925-00-890-8218



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-890-8218 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.250 inches **Body Length:** 2.203 inches **Body Width:** 2.250 inches **Body Height:** 2.125 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.187 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.743 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.182 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.486 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

NSN 5925-00-890-8218

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
11.000 at 200 pct all locations and 60.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
8.000 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
A030a0