

View Online at <https://aerobasegroup.com/nsn/5925-00-893-8566>

Overall Length:

5.250 inches

Overall Height:

3.660 inches

Overall Width:

1.500 inches

Case Material:

Plastic

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Thread Size:

0.164 inches

Trip Release Duty Cycle:

Continuous single location

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 150 pct single location and 5.000 at 150 pct single location and 0.350 at 200 pct single location and 1.270 at 200 pct single location and 0.120 at 300 pct single location and 0.250 at 300 pct single location and 0.050 at 400 pct single location and 0.160 at 400 pct single location and 0.030 at 500 pct single location and 0.090 at 500 pct single location and 0.020 at 600 pct single location and 0.060 at 600 pct single location and 0.020 at 700 pct single location and 0.050 at 700 pct single location and 0.010 at 800 pct single location and 0.030 at 800 pct single location and 0.010 at 900 pct single location and 0.030 at 900 pct single location and 0.010 at 1000 pct single location and 0.030 at 1000 pct single location

Special Features:

Mtg.Holes on 1 in.By 3.062 in.Mtg centers, w/one spot auxiliary switch

Frequency In Hertz:

400.0 single location

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0