

View Online at <https://aerobasegroup.com/nsn/5925-00-896-0347>

Overall Length:

6.218 inches

Overall Height:

2.750 inches

Overall Width:

3.406 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.219 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations and 15.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0