# NSN 5925-00-896-4264

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-896-4264

#### **Body Style:**

Multipole-single actuator type

#### **Body Length:**

3.750 inches

# Body Width:

2.000 inches

#### **Body Height:**

2.344 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

#### **Boss Height:**

0.156 inches

### Pole Quantity:

2

#### Arc Quenching Method:

Magnetic blowout

## Mounting Facility Type And Quantity:

2 clip

#### Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

75000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## **Reset Method:**

Manual

## Main Contact Tripping Mechanism Type:

Trip free

#### Manual Actuator Type And Quantity:

1 toggle

# NSN 5925-00-896-4264

Circuit Breaker - Page 2 of 2



**Actuator Function:** Trip-reset **Actuator Position Designation:** Between pole one and two Trip Delay Time In Seconds Per Rated Continuous Current: 13.000 at 200 pct all locations and 100.000 at 200 pct all locations Inclosure Protection Type For Which Designed: General purpose **Trip Release Ambient Tempurature Rating:** 40.0 degrees celsius all locations **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 2 clip and 2 compression Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0