

View Online at <https://aerobasegroup.com/nsn/5925-00-897-0354>

Case Material:

Plastic

Pole Quantity:

5

Mounting Facility Type And Quantity:

1 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 200 pct all locations and 0.600 at 200 pct all locations and 0.070 at 300 pct all locations and 0.200 at 300 pct all locations and 0.040 at 400 pct all locations and 0.100 at 400 pct all locations

Inclosure Protection Type For Which Designed:

Moisture resistant and fungus resistant

Special Features:

Equipped with relay trip on right coil

Frequency In Hertz:

400.0 all locations

Test Data Document:

13499-260-4047-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc

Terminal Type And Quantity:

12 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0