

View Online at <https://aerobasegroup.com/nsn/5925-00-899-3648>

**Body Style:**

Single pole type

**Bushing Length:**

0.315 inches

**Body Length:**

1.750 inches

**Body Width:**

0.625 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.687 inches

**Mounting Surface To Terminal End Distance:**

1.635 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.000 at 200 pct single location and 4.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Shockproof and vibrationproof and hermetically sealed

**Frequency In Hertz:**

60.0 single location

**Unpackaged Unit Weight:**

2.200 ounces

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0