

View Online at <https://aerobasegroup.com/nsn/5925-00-901-1651>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.125 inches

**Body Width:**

2.750 inches

**Body Height:**

3.031 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.225 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.250 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

70.0 amperes ac all locations and 70.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

14000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

4 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0