NSN 5925-00-903-2476

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-903-2476 **Body Style:** Single pole type **Body Length:** 3.344 inches **Body Width:** 1.000 inches **Body Height:** 2.312 inches **Case Material: Plastic Boss Height:** 0.188 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function: Trip-reset

NSN 5925-00-903-2476

Circuit Breaker - Page 2 of 2



Α	ctuator	Position	Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 200 pct single location and 300.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 clip and 1 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0