NSN 5925-00-906-7803

Circuit Breaker - Page 1 of 2

125.0 all locations



View Online at https://aerobasegroup.com/nsn/5925-00-906-7803

Body Style:
Multipole-single actuator type
Body Length:
11.000 inches
Body Width:
8.250 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
9.875 inches
Center To Center Distance Between Terminals Parallel To Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
9.875 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
3.000 inches
Boss Height:
0.250 inches
Mounting Surface To Terminal End Distance:
9.218 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
250.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
20000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

NSN 5925-00-906-7803 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Frip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct all locations and 180.000 at 200 pct all locations
nclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Ferminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A030a0