

View Online at <https://aerobasegroup.com/nsn/5925-00-910-7485>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

Between 1.954 inches and 1.984 inches

**Overall Height:**

Between 0.989 inches and 0.997 inches

**Overall Width:**

Between 1.329 inches and 1.359 inches

**Case Material:**

Plastic

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

500.0 milliamperes ac single location and 500.0 milliamperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

230.0 ac single location and 300.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

200.0 ac single location and 50.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location and 1.000 at 300 pct single location

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius single location

**Switch Terminal Type:**

Pin

**Switch Current Rating And Type In Amps:**

1.0 ac and 1.0 dc

**Switch Voltage Rating And Type In Volts:**

115.0 ac and 50.0 dc

**Frequency In Hertz:**

400.0 single location

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0