NSN 5925-00-912-2516

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-912-2516

| Body Style: |
|--|
| Single pole type |
| Overall Length: |
| 2.190 inches |
| Body Width: |
| 0.750 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.781 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.812 inches |
| Fragility Factor: |
| Moderately rugged |
| Mounting Surface To Terminal End Distance: |
| 1.380 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 10.0 amperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 28.0 dc single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 1000.0 dc single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Thermal single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 138.0 single location |
| Reset Method: |
| |
| Internal Trip Release Configuration: |
| Series trip single location |

NSN 5925-00-912-2516

Circuit Breaker - Page 2 of 2



Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and salt spray proof and fungus resistant

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Test Data Document:

81349-mil-c-13516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab w/screw

Specification Data:

81349--13516/5bii government specification

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A030a0