## NSN 5925-00-912-2549

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-912-2549

Body Style:	
Single pole type	
Body Length:	
3.719 inches	
Body Width:	
0.990 inches	
Case Material:	
Plastic	
Center To Center Distance Between Terminals Parallel To Length:	
3.063 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body	/ Length
2.750 inches	
Fragility Factor:	
Moderately rugged	
Boss Height:	
0.156 inches	
Mounting Surface To Terminal End Distance:	
3.239 inches	
Pole Quantity:	
1	
Arc Quenching Method:	
Magnetic blowout	
Mounting Facility Type And Quantity:	
2 threaded hole	
Storage Type:	
General purpose warehouse	
Special Handling Feature:	
Magnetic	
Thready Qty Per Inch (tpi):	
32	
Maximum Continuous Load Current Rating Per Pole:	
15.0 amperes ac single location	
Operating Voltage Type And Rating Per Pole In Volts:	
250.0 ac single location	
Maximum Interrupting Capacity Current Type And Rating Per Pole In	Amps:
1500.0 ac single location	
Circuit Protection Type:	
Overcurrent single location	
Trip Release Method:	
Magnetic-hydraulic single location	
Trip Release Characteristic:	

Time delay single location

## **NSN 5925-00-912-2549** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
35.000 at 200 pct single location and 105.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
0.690 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0