

View Online at <https://aerobasegroup.com/nsn/5925-00-912-2774>

Body Style:

Single pole type

Bushing Length:

Between 0.360 inches and 0.380 inches

Body Length:

Between 1.448 inches and 1.510 inches

Body Width:

Between 0.567 inches and 0.629 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.870 inches and 0.880 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 1.524 inches and 1.586 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

110.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.800 at 200 pct single location and 3.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof and fungus resistant and hermetically sealed

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0