NSN 5925-00-916-8585



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-916-8585 **Body Style:** Rectangular dimensional envelope **Overall Length:** 6.000 inches **Overall Height:** 1.375 inches **Overall Width:** 3.969 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.187 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location and 15.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 7500.0 ac single location and 5000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:**

Trip-reset

Actuator Position Designation:

At pole one

NSN 5925-00-916-8585

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct single location and 90.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 compression

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0