## NSN 5925-00-918-1483

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-918-1483

**Body Style:** Single pole type **Body Length:** Between 2.480 inches and 2.500 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** Between 1.925 inches and 1.955 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.050 inches and 2.070 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.135 inches and 0.165 inches **Mounting Surface To Terminal End Distance:** 2.491 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1500.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** 

Time delay single location

## **NSN 5925-00-918-1483** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.200 at 200 pct single location and 2.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Moisture resistant and salt spray proof and shock resistant and vibration resistant
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
3.700 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0