NSN 5925-00-918-1491

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-918-1491

Body Style:
Single pole type
Body Length:
2.530 inches
Body Width:
0.760 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.460 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length
2.062 inches
Boss Height:
0.150 inches
Mounting Surface To Terminal End Distance:
2.480 inches
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic single location
Trip Release Characteristic:
Instantaneous single location and time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:

Manual

NSN 5925-00-918-1491 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Reset
Internal Trip Release Configuration:
Relay trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.500 at 150 pct single location and 1.100 at 150 pct single location and 0.250 at 200 pct single location and 0.800 at 200 pct single
location and 0.100 at 300 pct single location and 0.200 at 300 pct single location
Inclosure Protection Type For Which Designed:
Explosion proof
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A030a0