NSN 5925-00-920-3098



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-920-3098 **Body Style:** Rectangular dimensional envelope **Overall Length:** 6.000 inches **Overall Height:** 3.406 inches **Overall Width:** 3.000 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.164 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations and 30.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations and 125.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations and 5000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:**

Trip-reset

Actuator Position Designation:

At pole one

NSN 5925-00-920-3098

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed: General purpose Trip Release Ambient Tempurature Rating: 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Terminal Type And Quantity: 4 compression Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A030a0