NSN 5925-00-920-6684

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-920-6684 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.500 inches **Body Height:** 3.594 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.125 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Boss Height:** 0.219 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations

Reset Method:

Manual

NSN 5925-00-920-6684

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0